



NOTES:

- MATERIAL:
 - HOUSING & COVER: HIGH TEMPERATURE THERMOPLASTIC WITH 30% G.F, UL94 V-0; COLOR: SEE NOTES 6
 - CONTACT: COPPER ALLOY;∅0.45mm
- FINISH:
 - CONTACT: GOLD PLATING(SEE TABLE)
- RECOMMENDED P.C.B THICKNESS : 1.6mm
- OTHER GENERAL SPEC. TO REFER : RJ45 SERIES SPEC.
- FOR WAVE SOLDERING LEAD-FREE PROCESS
- 10214-04220001-X X X X

- R: RoHS
- COLOR:
 - 1.HOUSING: BLACK
 - 3.HOUSING: YELLOW/114C
 - 8.HOUSING: ORANGE/1375C
- MATERIAL:
 - 3.HOUSING:PA46
- PLATING:
 - 2.CONTACT: Au 3u"

TABLE

3	10214-04220001-238R	Au3u"	PA46	1375C	RoHS
2	10214-04220001-233R	Au3u"	PA46	114C	RoHS
1	10214-04220001-231R	Au3u"	PA46	BLACK	RoHS
NO:	PART NO:	PLATING	MATERIAL	REMARK	REMARK

COPLIANCE WITH THE REQUIEMENT RoHS HF SONY00259 OTHER
 ※NO USING RESTRICTED AND BANNED SUBSTANCE

3	CONTACT	SEE PART DRAWING	SEE PART DRAWING	GOLD PLATED
2	COVER	SEE PART DRAWING	SEE PART DRAWING	UL 94V-0
1	HOUSING	SEE PART DRAWING	SEE PART DRAWING	UL 94V-0
NO:	DESCRIPTION	MATERIAL	COLOR	REMARK

CUSTOMER DRAWING		LITE Liteconn Co.,Ltd.	
-TOLERANCES- UNLESS OTHERWISE SPECIFIED		TITLE: RJ45圓針PORT口下階全塑 1X4PORT8P8腳柱3.3無鐵腳無彈片	
X.X ±0.35	X.X* ±3*	APPD:	DWG NO: 10214-04220001-XXXX
X.XX ±0.25	X.XX* ±2*	CHECK:	DATE: 2010.10.12
X.XXX ±0.15	X.XXX* ±1*	DRAW: 韋芳	SCALE: 1:1
			UNIT: MM
			PAGE: 1/1